

FENWICK & TILBROOK

THE PAINT AND COLOUR EXPERTS

Application

Claypaint

2% Sheen Flat Matt Finish

Fenwick & Tilbrook Claypaint is specially designed for interior use on limewash plastered interior walls and ceilings. Its unique formulation gives a highly breathable, yet durable flat matt surface.

PROPERTIES:

- Highly breathable
- Very low VOC content
- Water based
- Odour free
- Reduces condensation
- Discourages mildew growth
- Ease of application
- Covers 10 – 12 sq m per litre
- Outstanding durability

APPLICATION NOTES:

1. Thoroughly wash down and remove all flaking and defective coating.
2. Make good any cracks and defects. Use flexible fillers only.
3. Glossy painted surfaces must be sanded to a matt finish prior to applying the first coat. Avoid the inhalation of dust.
4. The surface must be clean and dry.
5. For any exposed-to-bare areas, apply one coat of Claypaint, thinned with water (one part water, nine parts paint).
6. Clay or lime plaster should be moistened prior to painting.
7. Apply two coats of Claypaint.
8. Bright or light colours may require additional coats.

DRYING TIMES

Touch dry in around one hour.

Interval between coats c.4 hours. Drying time 6 – 12 hours.

Based on 23°C ambient temperature, 50% relative humidity, 50 micron dry film thickness (DFT).

Temperature, humidity and thickness of coat will affect drying times. Do not apply at temperatures below 5°C.

APPLICATION METHODS

Suitable for application by brush, roller or airless spray.

PRIMING

Fenwick & Tilbrook paints are self priming. However, if a heavily repaired substrate has a variation of porosity and colours, priming is recommended as a first coat to create an even base colour. Prime new, bare and porous surfaces by using one coat of Fenwick & Tilbrook paint thinned with water (one part water, nine parts paint). Similarly, stains that may migrate through the paint should be treated with primer prior to painting.

CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE AND STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure, upright position.