

FENWICK & TILBROOK

THE PAINT AND COLOUR EXPERTS

Application

Multi-surface Primer

A water-based, multi-purpose bonding primer suitable for use on wood, masonry, metal, MDF, melamine, PVC and ceramic tiles. The low VOC water-based formulation is ideal for both interior and exterior use. It is ideally suited as a primer for Fenwick & Tilbrook Interior and Exterior Eggshell paint.

Available in White or Grey in 1 litre, 2.5 litre and 5 litre tins. It can also be tinted to match top coat colours.

USE

Stir thoroughly before use. Apply liberally and evenly by brush.

Preparation of the surface to be painted is vital to the performance of your Fenwick & Tilbrook paint. Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only. Wash down and remove old flaking or defective coating.

A glossy painted surface must be sanded to a matt finish prior to applying the first coat of Fenwick & Tilbrook paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.

Coverage approximately 12 sq m per litre.

It is touch dry in 1 hour and can be re-coated after four hours. Allow primer to fully dry before applying any finishing coat. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C.)

CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE AND STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure, upright position.