

# FENWICK & TILBROOK

THE PAINT AND COLOUR EXPERTS

## Application

### Ultimate Masonry

#### 15% Sheen Satin Finish

Fenwick & Tilbrook Ultimate Masonry is tough and self-priming, with a soft sheen and exceptional performance. Ultimate Masonry is suitable for all masonry surfaces.

Bare or loose masonry should be treated and sealed with a suitable acrylic primer before applying Fenwick & Tilbrook paint.

#### PROPERTIES:

- Outstanding durability
- Excellent elasticity allowing natural movement
- Extraordinary depth of colour
- Ease of application
- Covers up to 12 sq m per litre
- Extremely low odour
- Very low VOC content.

#### APPLICATION NOTES:

New plaster and porous surfaces:

1. The surface must be clean and dry.
2. Apply one coat of Ultimate Masonry as a sealing and priming coat.
3. Apply two coats of Ultimate Masonry.

Previously painted surfaces:

1. Thoroughly wash down and remove all flaking and defective coating.
2. Make good any cracks and defects.

3. Thoroughly rub down to create a matt surface.
4. The surface must be clean and dry.
5. For any exposed-to-bare areas, apply one coat of Ultimate Masonry as a sealing and priming coat.
6. Apply two coats of Ultimate Masonry.
7. Bright or light colours may require additional coats.

## **DRYING TIMES**

Touch dry in around 1 to 2 hours

Interval between coats c. 4 hours

*Based on 23°C ambient temperature, 50% relative humidity, 50 micron dry film thickness (DFT)*

*Temperature, humidity and thickness of coat will affect drying times*

## **APPLICATION METHODS**

Suitable for application by brush, roller or airless spray.

## **CLEAN UP**

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

## **STORAGE AND STABILITY**

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure, upright position.