

Description

A waterbased claypaint (2% sheen) available in the full Fenwick & Tilbrook palette, specially designed for interior use on plaster walls and ceilings. Its unique formulation gives a highly breathable, yet durable flat matt surface. It is low in VOC and is particularly suited for application onto lime plaster.

Available in 1 litre, 2.5 litre and 5 litre cans.

Use

Stir thoroughly before use. Apply two coats of Fenwick & Tilbrook paint by brush, roller or spray application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your Fenwick & Tilbrook paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate Fenwick & Tilbrook paint, thinned with water to ensure it is absorbed into the surface. Depending on the paint, up to a 50/50 ratio will ensure the paint is wet enough to be absorbed.
- Clay or lime plaster should be moistened prior to painting.

Coverage approximately 10m² per Litre. Touch dry in one hour, recoat after four hours.

Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

For airless spray application use nozzle tip 0.46 mm (0.018"), with a spray angle between 60° and 85°. Nozzle pressure to be 15-18 MPa (150-180 kg/cm²). Dilute with water as required.

Clean up

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

Storage and Stability

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

Health, Safety & Environmental Information

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents / container to waste disposal site in accordance with local / national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. If SWALLOWED call a POISON centre / doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing and seek medical advice. IF SPRAYING: Do not breathe spray. Wear respiratory protection.

PLEASE NOTE: Special precautions should be taken during surface preparation of pre-1960s paint surfaces as they may contain harmful lead.

VOCs

EU limit value for this product (Cat A/a): 30g/L (2010). This product contains max 30g/L VOC.

Other Information

For further advice or information regarding this product please contact Fenwick & Tilbrook direct or go to the website.

This product is produced in the UK by Fenwick and Tilbrook Ltd. Church Farm, Old Fakenham Road, Attlebridge, Norwich, Norfolk, NR9 5ST. Tel: 01362 684125. www.fenwickandtilbrook.com.