

Description

A waterbased, high performance, low sheen (15%) masonry paint available in the full Fenwick & Tilbrook palette, designed for use on all types of mineral surfaces, excluding common and fletton brick. The low VOC waterbased formulation gives exceptional exterior durability and extraordinary depth of colour.

Available in 1 litre, 2.5 litre and 5 litre cans.

Use

Stir thoroughly before use. Apply two coats of Fenwick & Tilbrook paint by brush, roller or spray application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your Fenwick & Tilbrook paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- Ensure all surfaces are clean, dry and free from dust, grease and dirt.
- Mould or fungal growth and powdery or porous surfaces should be treated before painting.
- Fenwick & Tilbrook paints are self-priming, therefore on virgin wood and surfaces previously painted in a water-based paint there is no need to prime. However, if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For exterior use, prime new, bare and porous surfaces.
- Do not apply externally if there is a risk of rain or frost, in very damp or humid conditions or where the temperature may fall below 8°C.
- Not suitable for common or fletton brick types.

Coverage approximately 10m² per Litre. Touch dry in 30 minutes, recoatable after two hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

For airless spray application use nozzle tip 0.46 mm (0.018"), with a spray angle between 60° and 85°. Nozzle pressure to be 15-18 MPa (150-180 kg/cm²). Dilute with water as required.

Clean up

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

Storage and Stability

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

Health, Safety & Environmental Information

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents / container to waste disposal site in accordance with local / national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. If SWALLOWED call a POISON centre / doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing and seek medical advice. IF SPRAYING: Do not breathe spray. Wear respiratory protection.

PLEASE NOTE: Special precautions should be taken during surface preparation of pre-1960s paint surfaces as they may contain harmful lead.

VOCs

EU limit value for this product (Cat A/c): 40g/L (2010). This product contains max 30g/L VOC.

Other Information

For further advice or information regarding this product please contact Fenwick & Tilbrook direct or go to the website.

This product is produced in the UK by Fenwick and Tilbrook Ltd. Church Farm, Old Fakenham Road, Attlebridge, Norwich, Norfolk, NR9 5ST. Tel: 01362 684125. www.fenwickandtilbrook.com