

FENWICK & TILBROOK

THE PAINT AND COLOUR EXPERTS

Application

Exterior Eggshell

20% Sheen – Satin Finish

Fenwick & Tilbrook Exterior Eggshell is tough and self-priming, with a soft sheen and excellent resilience.

Exterior Eggshell is suitable for woodwork, plaster, masonry and metalwork.

Bare metal should be treated with a suitable primer, ideally Fenwick & Tilbrook Multi-purpose Primer, before applying Fenwick & Tilbrook paint.

Surfaces previously painted in an oil-based product must be sanded back and primed prior to painting. We recommend Fenwick & Tilbrook Multi-purpose Primer.

PROPERTIES:

- Outstanding durability
- Excellent elasticity, allowing natural movement
- Extraordinary depth of colour
- Ease of application
- Covers up to 12 sq m per litre
- Extremely low odour
- Very low VOC content.

APPLICATION NOTES

New and porous surfaces:

1. The surface must be clean and dry.
2. Apply one coat of Exterior Eggshell as a sealing and priming coat.
3. Apply two coats of Exterior Eggshell.

Previously painted surfaces:

1. Thoroughly wash down and remove all flaking and defective coating.
2. Make good any cracks and defects.
3. Thoroughly rub down to create a matt surface.
4. If previously painted in an oil-based product, a primer must be applied.
5. The surface must be clean and dry.

6. Apply two coats of Exterior Eggshell.
7. Dark colours may require additional coats.

DRYING TIMES

Touch dry in around 1 hour

Interval between coats c. 2 hours

Based on: 23°C ambient temperature, 50% relative humidity, 50 micron dry film thickness (DFT).

Temperature, humidity, ventilation and thickness of coat will affect drying times.

APPLICATION METHODS

Suitable for application by brush, roller or airless spray.

PRIMING

Fenwick & Tilbrook paints are self-priming. However, if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour. Prime new, bare and porous surfaces using one coat of Fenwick & Tilbrook paint, thinned with water (one part water, nine parts paint).

CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE AND STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure, upright position.