

# FENWICK & TILBROOK

THE PAINT AND COLOUR EXPERTS

## Application

### Interior Eggshell

#### 10% Sheen – Matt Finish

Fenwick & Tilbrook Interior Eggshell is a tough, self-priming paint with a soft and delicate sheen.

Interior Eggshell is suitable for woodwork, plaster, masonry and metalwork.

Bare metal and oil-based surfaces should be treated with a suitable primer, ideally Fenwick & Tilbrook Multi-purpose Primer, before applying Fenwick & Tilbrook paint.

#### PROPERTIES:

- Outstanding durability
- Extraordinary depth of colour
- Ease of application
- Covers up to 10 sq m per litre
- Extremely low odour
- Very low VOC content.

#### APPLICATION NOTES

New plaster and porous surfaces:

1. The surface must be clean and dry.
2. Apply one coat of Interior Eggshell, thinned with water.
3. Apply two coats of Interior Eggshell.

Previously painted surfaces:

1. Thoroughly wash down and remove all flaking and defective coating.
2. Make good any cracks and defects.
3. Thoroughly rub down to create a matt surface.
4. The surface must be clean and dry.
5. For any exposed-to-bare areas, apply one coat of Interior Eggshell, thinned with water
6. Prime any oil coated surfaces and lightly sand.
7. Apply two coats of Interior Eggshell.
8. Bright or light colours may require additional coats.

## **DRYING TIMES**

Touch dry in around 1 hour.

Interval between coats c. 2 hours.

*Based on: 23°C ambient temperature, 50% relative humidity, 50 micron dry film thickness (DFT).*

*Temperature, humidity, ventilation and thickness of coat will affect drying times.*

## **APPLICATION METHODS**

Suitable for application by brush, roller or airless spray.

## **PRIMING**

Fenwick & Tilbrook paints are self-priming. However, if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour. Prime new, bare and porous surfaces using one coat of Fenwick & Tilbrook paint, thinned with water.

## **CLEAN UP**

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

## **STORAGE AND STABILITY**

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure, upright position.